



CO-800

Automatic Rotary Seed Coater

- **LARGE CAPACITY, HIGH THROUGH-PUT, FULLY AUTOMATIC SEED COATER.**
- **SUITABLE FOR BOTH FILM AND PELLET COATING.**
- **QUALITY COMPONENTS, SOLID, DEPENDABLE, AUSTRALIAN MADE.**



SPECIFICATIONS:

Coater Type	Rotary Coater 800mm
Motor	WEG / TECO
Controller	PLC – All Functions (OMRON)
Discharge Door (Seed Exit)	Air Operated
Liquid Applicator(s)	via Peristaltic Pump(s) onto Spinning Disk
Powder Application	Flexible Hopper Powder Feeder (Standard Length Screw)
Rotor Air Seal	Positive Air Pressure Under Rotor

WEIGH SCALE FEATURES:

Vibrator	Stainless Steel 'In Feed' Seed Tray
Discharge Hopper	Raw Seed – Stain. Steel with Air Actuated Door
Load Cell	For Mounting of the Discharge Hopper
Vibration Control	PLC
Load Cell Control	PLC

DIMENSIONS:

Batch Quantity	20 > 40 Kg
Coating Drum Size	800mm Diameter X 680mm High
Machine Size	W 1000mm X L 1000mm X H 1200mm
Powder Hopper Volume	Approx. 30lt
Total Weight	600kg
Rotor Motor (Coater)	7.5kW
Spinning Disk Voltage	415 VAC
Power Source	415 AC, Three Phase
Manufactured	Melbourne, Australia

Centor Oceania offer a growing range of seed coating materials in both liquid and powder forms. Our products can be used for Film-Coating, Encrusting and Pelleting.


To learn more about any of the products in the Centor Oceania - Seed Applied Coating range or Seed Coating & Drying Machinery, please call: **0448 725 266**

ALSO AVAILABLE IN MANUAL AND SEMI-AUTO MODELS.

Centor Oceania

76 Colemans Road Carrum Downs, Vic. 3201

T: 03 8779 2170 info@centoroceania.com www.centoroceania.com




Centor Oceania
"Your one stop global seed tech shop"