



RFBD600-12 Rotary Fluid Bed Dryer Ø600mm

Average capacity drying system to keep up with HR600 rotary coating process

The RFBD600-12 system is the first rotary fluid bed dryer size used for commercial production. The RFBD600-12 is available in different lengths and is capable to keep up with the fast process of the HR600 rotary coater. See also our special Integrated Coating Drying Systems catalogue for complete coating/drying installations.

Standard equipped with:

- Manual operated version
- Capacity from 20kg/h encrusting (based on 10 minutes processing time) to 600kg/h basic seed treatment (based on 15 seconds processing time, and 3kg of seeds/batch)
- Frequency controlled process fan
- Frequency controlled drying time
- Cooling fan
- Vibrating seed feed system
- Fully Self cleaning system

Options

- PLC and Touch panel controlled system
- Adaption to your already used rotary coating system
- Several air conditioning options available (depending on your process)
- Cooling unit for cool air supply to cooling fan

Due to the variety of coating processes and humidity conditions of your specific business we configure the dryers based on our test equipment. Ask us for more information about a dryer for your specific process.



First commercial plant in Made Holland, HR600ASFC with RFBD600-12 dryer (ICDS600), including recirculation and cooling section. After the process the seeds are ready for packaging. Capacity up to 400kg/h film coating

For further information contact:



76 Colemans Road,
Carrum Downs,
Victoria, 3201 Australia

Ph: +61 3 8779 2170
www.centoroceania.com